

In The Specification:

Please substitute the corresponding paragraphs in the specification with the following:

[0010] FIG. 1 is a perspective view of a front seat assembly for an RV in accordance with an embodiment of the present invention, when a seatback of a middle seat is folded, ~~and~~

[0011] FIG. 2 is a perspective view of the RV front seat assembly in accordance with an embodiment of the present invention, when the seatback of the middle seat is unfolded; and

[0015] As shown in FIG. 1, an armrest 135 is formed behind the seatback 134 so that the driver can rest her/his arm thereon. It is preferred that the armrest 135 is formed together with the seatback 134 in one body. More preferably, an armrest (~~not shown~~) for a passenger, sitting on the assistant seat 110, is also formed behind the seatback 134 of the middle seat 130 such that the passenger can rest their left arm thereupon, as shown in FIG. 3. Consequently, the width of the seatback 134 of the middle seat 130 can be substantially a full seat width. Also, as shown in FIG. 2, a headrest 136 is installed in the upper portion of the seatback 134 of the middle seat 130.

[0016] In accordance with an embodiment of the front seat assembly constructed as above, if there is no passenger sitting on the middle seat 130, the seat cushion 132 is unfolded and the seatback 134 is folded, as shown in FIG. 1. In this configuration, the driver can rest her/his right arm on the armrest 135 formed behind the seatback 134 of the middle seat 130. Furthermore, in a preferred embodiment, the assistant can rest his/her left arm on the armrest (~~not shown~~) formed behind the seatback 134 of the middle seat 130, as shown in FIG. 3. If a third seat is needed to accommodate another passenger, the middle seatback 134 is unfolded as shown in FIG. 2.

Please add the following New paragraph after paragraph [0011]:

[0012] FIG. 3 is a perspective view of the RV front seat assembly in accordance with an another embodiment of the present invention, when the seatback of the middle seat is folded.

In The Drawings:

Please include new FIG. 3 with the original FIGS. 1 and 2.